



RKD BEARING LLC



LSE315BRHSNQATL Bearing 2D drawings and 3D CAD models

3.938 Inch | 100.025 Millimeter x 3.346 Inch | 85 Millimeter x 4.921 Inch | 125 Millimeter Timken LSE315BRHSNQATL Split Roller Bearing Cartridges

Bearing No. LSE315BRHSNQATL

| | |
|---------------------------|--|
| Category | Pillow Block Bearings |
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 28.71 |
| EAN | 0013992056061 |
| Product Group | B04144 |
| Number of Mounting Holes | 2 |
| Mounting Method | Clamp Collar |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-Expansion |
| Mounting Bolts | 24 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | LSE315BR |
| Seals | Triple Lip Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch - Metric | Inch |
| Other Features | Single Row Light Duty With Support Wide Inner Ring |
| Category | Pillow Block Bearings |
| UNSPSC | 31171511 |
| | |



RKD BEARING LLC

| | |
|-------------------------------|---|
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer URL | http://www.timken.com |
| Weight / LBS | 63.23 |
| Bolt Spacing Minimum | 0 Inch 0Millimeter |
| B | 4.921 Inch 125 Millimeter |
| Nominal Bolt Center to Center | 13.9 Inch 354 Millimeter |
| Bolt Spacing Maximum | 0 Inch 0Millimeter |
| D | 3.346 Inch 85 Millimeter |
| Actual Bolt Center to Center | 13.9 Inch 354Millimeter |
| d | 3.938 Inch 100.025 Millimeter |
| Shaft Size | 3-15/16 in |
| Seal Type | Aluminium Triple Labyrinth |
| Bearing Type | Split Cylindrical Retained Type |
| Support Type | Two-Bolt Plummer Block |
| Series Type | Light Series |
| Pillow/Plummer Block Style | Split Cylindrical Housed Unit - Angled |
| Bolt Size | 2 x M24 |
| Dimension H | 125 mm |
| Dimension H2 | 265 mm |
| Dimension J | 350 mm |
| Dimension L | 410 mm |
| Dimension M | 120 mm |
| Housing Width | 5.3 in |
| Cr - Dynamic Load Rating | 64745 lbf |
| Cor - Static Load Rating | 82280 lbf |
| Ca - Axial Load Rating | 3596.90 lbf |
| | |



RKD BEARING LLC

| | |
|---------------|---|
| Maximum Speed | 2340 rpm |
| Note | This product line was formerly known as "Revolvo" |